

A Ferragon Company



(216) 671-6161

11103 Memphis Ave., Brooklyn, OH 44144

PROCESSING CAPABILITIES



Low Carbon, High Carbon, HSLA, Alloy, Ferritic Stainless, Others		Gauge	Width	Length	ID	OD	Max Weight	Condition
Combination Reversing Mill	Inbound	.017/.250"	24"-60"	Coil	24" Only	36"-74"	72,000#	HR P&O and CR
	Outbound	.015/.250"	24"-60"	Coil	24" Only	36"-74"	72,000#	Cold Reduced, Temper Rolled, Skin Pass

Low Carbon, High Carbon, HSLA, Alloy, Ferritic Stainless, Others		Gauge	Width	Length	ID	OD	Max Weight	Temperature
Hydrogen Anneal	Inbound	.015" Min	14" Min	Coil	24" Min	44" - 72"	60,000#	Up to 1562° F (850° C)
	Outbound	.015" Min	14" Min	Coil	24" Min	44" - 72"	60,000#	

Low Carbon, High Carbon, HSLA, Alloy, Ferritic Stainless, Others		Gauge	Width	Length	ID	OD	Max Weight	Condition
Pickler	Inbound	.060/.500"	24"-72"	350' Min	20"-32"	44"-76"	80,000#	HR, Stainless 400
	Outbound	.060/.500"	72" Max up to .375" 60" Max up to .500" 48" Max up to .625"	Coil	24" Only	44"-76"	60,000#	P&O Pickle Dry Pickle Shot Blast
Hot Rolled Slitter	Inbound	.125/.700"	15"-76"	Coil	20"-32"	36"-80"	80,000#	HR or HR P&O
	Outbound	.125/.700"	3"-72" (under 6" by inquiry)	Coil	24" or 28"	36"-76"	80,000#	✓

Hot-Dipped and Electro Galvanized, Ultra Low Carbon, AHSS grades up to MS1700, Stainless, and Aluminum		Gauge	Width	Length	ID	OD	Max Weight	Condition
Cold Rolled Slitter	Inbound	.015"-.156"	24"-80"	Coil	24"	30"-84"	70,000#	CR, HD, EG, AHSS, Stainless, Aluminum
	Outbound	.015"-.156"	2"-78"	Coil	20" or 24"	30"-84"	70,000#	Oil/Prelube, Top & Bottom Inspection

216.671.6161
www.ferrousmetalprocessing.com

A Ferragon Company

